

TTP eco

Thermal-transfer printer



*The versatile **TTP eco** thermal-transfer printer is designed for marking and labelling solutions in systems and switchgear cabinet applications. It offers an economical alternative for easily printing the **CONTA-CLIP GKE** and **KKE** label rolls.*

The printer prints either by direct thermal printing or via thermal transfer. Label rolls and colour ribbons can be changed quickly and easily thanks to the generously sized housing cover.

In spite of the compact size of the housing, the printer can be fitted with label rolls up to 127 mm (5") wide, and with colour ribbons up to 300 m long. Printer down time during the replacement of consumables is therefore reduced and productivity is increased.

TTP eco Thermal-transfer printer

Order information and technical documentation

TTP eco Thermal-transfer printer

- Its speed and durability make the **TTP eco** printer ideal for industrial applications.
- Loading times for different print variations are short, thanks to fast and straightforward exchange of label rolls.
- The accompanying labelling software, **CONTA-Sign CS**, is available in ten languages (German, English, French, Spanish, Hungarian, Italian, Dutch, Polish, Russian, Swedish).
- Free software updates can be downloaded from our web page.
- The **TTP eco** can be used to print on **GKE** and **KKE** labels quickly and simply.

TTP eco



Type

Type

Cat. no.

Technical data

Printer type

Intended use

Diameter of label role core

Max. diameter of roll

Max. label width

Min. label width

Print width

Max. printing height

Min. label height

Resolution

Max. printing speed

Push button

Interfaces

Bar codes

Dimensions (W x H x D)

Weight

Supply voltage

Power consumption

Operating conditions

Ambient temperature

Relative humidity

TTP eco accessories

Cat. no.	Typ	Qty.p.pck.
1641.0	TTP Film	1
1639.0	TTP Cleaning set	1
17742.0	TTP eco Cutting knife	1
17743.0	TTP eco External unwinder	1

Qty.p.pck.

1

TTP eco Starter Kit

1xTTP eco Printer (**17740.0**)

1xTTP-Film (**1641.0**)

Thermal-transfer printer **TTP eco**: including power cable, printer driver and **CONTA-Sign CS** software in ten languages (German, English, French, Spanish, Hungarian, Italian, Dutch, Polish, Russian, Swedish), runs under Windows: XP, Vista, 7. Connecting cable (USB interface cable)

17741.0

Thermal transfer

Label printing

25.4 mm / 38.1 mm / 76.2 mm

127 mm

118 mm

25 mm

104 mm

850 mm

12 mm

203 dpi

50 - 100 mm/sec

Flat type

RS232 C / USB 1.1 / Parallel Centronics (SPP)

EAN 8, EAN 13, EAN 128, Code 39, Code 39 extended, Code 128, Code 2/5 interleaved

226 mm x 171 mm x 285 mm

approx. 3 kg

110–230 V AC 50–60 Hz

Max. 70 VA

+ 5 to + 35 °C

Operation: max. 80%, Storage: max. 90%

Short description

Roll of thermal-transfer film, 110 mm x 300 mm (outside with colour), industrial quality

1 print head and drum cleaner, 250 ml

1 compressed air for cleaning the photoelectric sensor, 200 ml

22 wipes, 5 cleaning spatulas, 2 cleaning cards, 1 cleaning foil for print head,

1 label-solvent spray, 200 ml

Automatically cuts labels after the printing process

External unwinder for maximum outer roll diameters of 250 mm; required for the **GKE** labels **3916.0**, **3906.0** and the **KKE** labels **3955.8**, **3955.7**.



17742.0

TTP eco Cutting knife



17743.0

TTP eco External unwinder